

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局



(43) 国际公布日:
2005年5月26日(26.05.2005)

PCT

(10) 国际公布号:
WO 2005/048613 A1

(51) 国际分类号: H04Q 7/20
(21) 国际申请号: PCT/CN2003/000952
(22) 国际申请日: 2003年11月12日(12.11.2003)
(25) 申请语言: 中文
(26) 公布语言: 中文

(81) 指定国(国家): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW

(71) 申请人(对除美国以外的所有指定国): UT斯达康(中国)有限公司(UTSTARCOM (CHINA) CO., LTD.) [CN/CN]; 中国北京市东城区东长安大街1号东方广场东方经贸城东二办公楼10层, Beijing 100738 (CN).

(84) 指定国(地区): ARIPO专利(BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI专利(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

(72) 发明人;及
(75) 发明人/申请人(仅对美国): 刘晟(LIU, Sheng) [CN/CN]; 赵柏峻(ZHAO, Baijun) [CN/CN]; 中国广东省深圳市南山区高新技术园区联想大厦三层, Guangdong 518057 (CN).


本国际公布:
— 包括国际检索报告。

(74) 代理人: 中国国际贸易促进委员会专利商标事务所 (CCPIT PATENT AND TRADEMARK LAW OFFICE); 中国北京市阜成门外大街2号万通新世界广场8层, Beijing 100037 (CN).

所引用双字母代码和其它缩写符号, 请参考刊登在每期PCT公报期刊起始的“代码及缩写符号简要说明”。

(54) Title: PACKET DATA UNITED DISPATCH PERFORMING METHOD AND APPARATUS IN DOWN-LINK MULTIPLE-CHANNEL OF THE MOBILE COMMUNICATION SYSTEM

(54) 发明名称: 移动通信系统中下行链路多信道分组联合调度的方法和装置



1 CORE NETWORK

(57) Abstract: The present invention relates to a method for packet data united dispatch on special channel in down-link of the UMTS, which comprises: a) before each DCH dispatch cycle, selecting transmission format of each DPCH so as to defining usable transmission format aggregate, according to restrict of DCH united packet data dispatching; b) restricting the total down-link transmitting power of DCH used in no-real time packet service not more than the dispatching power of the down-link total power in the dispatch cycle; c) defining the corresponding weight value of each DC in united packet data dispatch performing according to the impartiality of DCH transmission and Oos request of DCH service; d) operating 0-1 arithmetic, calculating the maximum bits which each DCH can dispatch and output. By the result of the step a), b), c), the present invention optimizes the special channel and maximizes the data throughput of the special channel.

[见续页]

UNAVAILABLE COPY